

---

## → MANUAL – DISPLAY STYLE: **Tabbed view**

---

*This will show a custom tabbed style for your data-sheet, more info, reviews, ... .*

### 1. Disable the following html code in “your\_webshop/themes/your\_theme/product.tpl”

1. “Data sheet”
2. “More info”
3. “HOOK\_PRODUCT\_TAB” & “HOOK\_PRODUCT\_TAB\_CONTENT”

### 2. Adding hook to “your\_webshop/themes/your\_theme/products-comparison.tpl”

- search for “{\$HOOK\_EXTRA\_PRODUCT\_COMPARISON}” and place this above the code.
- {hook h='comparisonMarkerCode'}

---

## → MANUAL – DISPLAY STYLE: **Theme view**

---

*This will allow you to keep your own product page style. Only the datasheet code will be added tot the product page.*

### 1. Search the code below in “your\_webshop/themes/your\_theme/product.tpl:”

{if isset(\$features) && \$features}

### 2. Replace the following code

- ❖ **Replace the code:** <table> ... </table>
- ❖ **With this hook:** {hook h='dsp' mod='datasheetpro'}

### 3. Adding hook to “your\_webshop/themes/default-bootstrap/products-comparison.tpl”

- search for “{\$HOOK\_EXTRA\_PRODUCT\_COMPARISON}” and place this above the code.
- {hook h='comparisonMarkerCode'}

---

## → MANUAL – Multiple Features display - **Follow these steps in order to display multiple features**

---

*In order see the multiple features in the Blocklayered module you need to thake following steps:*

1. **Open file:** /modules/blocklayered/blocklayered.php
  - **Change (6 times):** '.\_DB\_PREFIX\_.'feature\_product
  - **To:** '.\_DB\_PREFIX\_.'MFV\_feature\_product
  - **Change (1 time):** \$sql\_query['group'] = 'GROUP BY fv.id\_feature\_value ';
  - **To:** \$sql\_query['group'] = 'GROUP BY fv.id\_feature\_value ORDER BY fv.value ASC ';
  - **Change (1 time):** GROUP BY fv.id\_feature\_value';
  - **To:** GROUP BY fv.id\_feature\_value ORDER BY fv.value ASC';

---

## → MANUAL – Multiple Features - THIS STEPS ARE ONLY NEEDED FOR PRESTASHOP 1.7+

---

In order to use multiple features in prestashop 1.7 you need to thake following steps:

### 1. Open file: /src/PrestaShopBundle/Model/Product/AdminModelAdapter.php

#### • Change:

```
//map features
if (!empty($form_data['features'])) {
    foreach ($form_data['features'] as $dataFeature) {
        $idFeature = $dataFeature['feature'];

        //custom value is defined
        if ($dataFeature['custom_value'][$this->defaultLocale]) {
            foreach ($this->locales as $locale) {
                $form_data['feature_'.$idFeature.'_value'] = null;
                $form_data['custom_'.$idFeature['_'.$locale['id_lang']] =
                $dataFeature['custom_value'][$locale['id_lang]];
            }
        } elseif ($dataFeature['value']) {
            $form_data['feature_'.$idFeature['_value']] = $dataFeature['value'];
        }
    }
}
```

#### • To:

```
//map features
if (!empty($form_data['features'])) {
    $n = 0;
    foreach ($form_data['features'] as $dataFeature) {
        $idFeature = $dataFeature['feature'];

        //custom value is defined
        if ($dataFeature['custom_value'][$this->defaultLocale]) {
            foreach ($this->locales as $locale) {
                $form_data['feature_'.$idFeature['_value_'.$n]] = null;
                $form_data['custom_'.$idFeature['_'.$locale['id_lang']] =
                $dataFeature['custom_value'][$locale['id_lang]];
            }
        } elseif ($dataFeature['value']) {
            $form_data['feature_'.$idFeature['_value_'.$n]] = $dataFeature['value'];
        }
        $n += 1;
    }
}
```

---

## → TROUBLESHOOTING:

---

### WHITE PAGE, ERRORS:

If you have a white page, or receive any kind of error, we recommend you to contact us. But before you do, take a moment through the following steps.

1. Open file: /config/defines.inc.php
2. Search: `define('_PS_MODE_DEV_', false);`
3. Change “false” to “true”
4. Go to the page with the problem, if there is an error code, you can send it to our support via prestashop.

### COMMON ISSUES:

Make sure that **NO** is selected for “Advanced Parameters” → “Performance” → “Disable all overrides”